


MDTE Series

Wire Wound Molded SMD Power Inductors

Size 7070



FEATURES




- [? ?] [? ? ?]
- [? ?] [?] [? ?] [? ?] [? ?] [? ?]
- [?] [? ?] [? ? ?] [? ? ?] [? ? ?] [?] [? ?] [? ?] [? ?] [? ?]
- [? ?] [? ?] [? ? ?]
- [?] [?] [?] [?] [?] [?] [? ?] [? ?]
- [? ?] [? ?] [? ?] [?] [?] [?] [? ?] [? ?] [? ?] [? ?] [? ?]
- [? ?] [? ?] [? ?]

APPLICATION

- [? ?] [?] [?] [?] [?] [?] [? ?]
- [?] [?]

Dimensions: [mm]

Land Pattern: [mm]




Electrical Properties:

Part No	Inductance	Tolerance				D

Saturation Current will cause L to drop approximately 30%

Temperature Rise Current: The actual value of DC current when the temperature rise is


Soldering Reflow:



Preheat condition: 150 ~200°C / 60~120 sec.
 Allowed time above 217°C: 60~90 sec.
 Max temperature: 260°C.
 Max time at max temperature: 10 sec.
 Allowed Reflow time: 2x max.


Packaging Information:

Tape Dimension:



Series	A0 (mm)	B0 (mm)	D (mm)	P0 (mm)	P1 (mm)	W (mm)	K0 (mm)	E (mm)	T (mm)
MDTE7070	8.2±0.1	8.0±0.1	1.5±0.1	4.0±0.1	12.0±0.1	16.0±0.3	7.3±0.1	1.75±0.1	0.35±0.05

Peel force of top cover tape:



The peel force of top cover tape shall be between 0.1 to 1.3 N

Product Marking:

Marking	Printing (Inductance)
---------	-----------------------

Reel Dimension: [mm]



Packaging Quantity: